



QNAP TS-432X-4G

Cena	3 399,00 zł
Dostępność	Na zamówienie
Numer katalogowy	QNA_TS432X4G
Kod producenta	TS-432X-4G
Kod EAN	4711103085202
Producent	QNAP
Porty 1GbE RJ-45	2
Port 10 GbE	1
Pamięć RAM	4GB

Opis produktu



QNAP TS-432X-4G

Dzięki modelowi TS-432X możesz wykorzystać pełen potencjał 4-zatokowego NAS i **prędkość 10GbE!** To wielofunkcyjne rozwiązanie pamięci masowej oferuje **bezpieczne tworzenie kopii zapasowych**, szybką transmisję, obsługę aplikacji kontenerowych i wiele innych funkcji. Ekonomiczny, a jednocześnie wydajny model TS-432X usprawnia przepływ pracy bez przekraczania budżetu.

Cechy wyjątkowe dysku sieciowego **QNAP TS-432X:**

- Wydajny cztero dyskowy **serwer plików** dla małych firm i biur domowych
- Serwer **TS-432X** zapewnia doskonałą prędkość odczytu na poziomie **1181 MB/sek** i zapisu na poziomie **887 MB/sek**
- Panel użytkownika i oprogramowanie dostępne w języku polskim
- Obsługa szyfrowania **256-bitowego AES**
- Dostęp do danych za pomocą aplikacji mobilnych z telefonu lub tabletu
- TS-432X wyposażony jest w gniazdo **PCIe Gen 3 x 4**, obsługujące różne karty rozszerzeń, aby zmaksymalizować wszechstronność aplikacji
- TS-432X obsługuje również **Time Machine dla komputerów Mac**
- Obsługa różnych protokołów, takich jak **Rsync, FTP i CIFS** do tworzenia kopii zapasowych różnych serwerów plików.
- Model TS-432X jest wyposażony w kompleksowe ustawienia uprawnień i środki ochrony, **które blokują złośliwe ataki i zapewniają bezpieczeństwo danych** na serwerze NAS
- **Dwa porty USB 3.2 Gen 1 (5 Gb/s)** z obsługą szybkiego kopiowania umożliwiając szybsze tworzenie kopii zapasowych na/z urządzeń USB
- Możliwość zbudowania systemu **monitoringu** z kamerami IP

Podstawowe funkcje **dysku sieciowego QNAP** dla domu:

Dostęp do danych w domu oraz z dowolnego miejsca na świecie.

System QNAP zapewnia szybki, a przede wszystkim bezpieczny sposób na udostępnianie danych każdemu i wszędzie. Dzięki aplikacji File Station oraz wbudowanemu **serwerowi VPN** można przeszukiwać, organizować i przenosić pliki pomiędzy QNAP, a dowolnym urządzeniem w sieci.




Udostępnianie plików dla każdej platformy Windows, MAC czy Linux.



Bezpieczeństwo danych.

Niezależnie od tego, gdzie przechowujesz swoje wrażliwe dane, nieuczciwe osoby zawsze próbują wykorzystać słabości systemu. Na pomoc przychodzą dyski sieciowe QNAP. Dzięki wbudowanemu kontrolerowi RAID, **wbudowanemu szyfrowaniu**, programowi antywirusowemu oraz zaawansowanej kontroli dostępu zabezpieczymy swoje dane przed ich utratą.



Monitoring video.

Zmień TS-432X w profesjonalny, wielofunkcyjny serwer NAS do monitoringu, który jest kompatybilny z ponad 8000 kamer IP i kamerami zgodnymi ze **standardem ONVIF**.

Dowiedz się więcej na temat systemu QNAP QTS:



Produkt posiada dodatkowe opcje:

Rozszerzenie gwarancji do 5 lat: Gwarancja Standard - 2 lata , Gwarancja QNAP rozszerzona do 5 lat [EXTW-GREEN-3Y] (+ 449,00 zł)

Pamięć RAM: 4 GB , 8 GB (+ 529,00 zł) , 16 GB (+ 1 059,00 zł)

Specyfikacja sprzętowa

Procesor	AnnapurnaLabs, firma Amazon, Alpine AL524, 4-rdzeniowy, 2,0GHz
	Architektura procesora
	64-bitowy ARM
	Koprocesor arytmetyczny FPU
	Tak
	Mechanizm szyfrowania
	Tak
	Pamięć systemowa
	4 GB SODIMM DDR4 (1 x 4 GB)
	Maksymalna pojemność pamięci
	16 GB (1 x 16 GB)
	Gniazdo pamięci
	1 x SODIMM DDR4
	Obsługa pamięci ECC
	Pamięć flash
	512 MB (ochrona systemu operacyjnego przed podwójnym
	Wnękę dysków
	4 dyski 3,5-calowe SATA 6 Gb/s, 3 Gb/s
	Kompatybilność dysków
	3,5-calowe zatoki:
	3,5-calowe dyski twarde SATA
	2,5-calowe dyski twarde SATA
	2,5-calowe dyski SSD SATA
	Wymieniany podczas pracy
	Tak
	Obsługa przyspieszenia pamięci podręcznej
	Tak
	SSD
	Port 2,5 Gigabit Ethernet (2,5G/1G/100M)
	2 (2,5G/1G/100M)
	Port 10 Gigabit sieci Ethernet
	1 x 10GbE SFP+
	Wake on LAN (WOL)
	Tak
	Ramka Jumbo
	Tak
	Gniazdo PCIe
	1
	Gniazdo 1: PCIe Gen 3 x4
	Wymiary kart dla gniazda PCIe 190 x 68,9 x 18,76 mm / 7,2
	2
	Port USB 3.2 Gen 1
	Kształt
	Tower
	Wskaźniki LED
	Zasilanie, stan, LAN, USB, HDD1-4
	Przyciski
	Zasilanie, reset, automatyczne kopiowanie USB
	Wymiary (wys. x szer. x gł.)
	226,5 x 170 x 165 mm
	Waga (netto)
	1.99 kg
	Waga (brutto)
	4.8 kg

Temperatura robocza	0-40°C
Temperatura przechowywania	-20-70°C
Wilgotność względna	5-95% bez kondensacji, temperatura mokrego termometru
Zasilacz	Zasilacz 90 W (12 VDC), 100-240 VAC
Wentylator	1 x 120mm, 12VDC
Ostrzeżenie systemowe	Brzęczyk
Gniazdo bezpieczeństwa Kensington	Tak
Standardowa gwarancja	2

Specyfikacja oprogramowania

Operating System	QTS 5.1.7
Supported Client Operating Systems	1. Apple Mac OS 10.10 or later 2. Ubuntu 14.04, CentOS 7, RHEL 6.6, SUSE 12 or later Linux 3. IBM AIX 7, Solaris 10 or later UNIX 4. Microsoft Windows 7, 8, 10 and 11 5. Microsoft Windows Server 2008 R2, 2012, 2012 R2, 2016, 2019 and 2022
Supported Browsers	1. Apple Safari (latest version) 2. Google Chrome (latest version) 3. Microsoft Edge (latest version) 4. Mozilla Firefox (latest version)
Supported Languages	Chinese (Traditional & Simplified), Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese (Brazil), Romanian, Russian, Spanish, Swedish, Thai, and Turkish
Storage Pool	Tak
SED Storage Pool	Tak
Maximum Pool size	308 TB
Maximum number of storage pool	128
Volume Type	Thick, Thin, Static
Maximum volume size	250 TB
Maximum number of volume	Note: At least 4 GB RAM is required. 128
Maximum shared folder size	250 TB
Maximum number of shared folder	512
JBOD Expansion	Tak
VJBOD / VJBOD Cloud	Tak
iSCSI Service	Tak
Fibre Channel Service	Tak
LUN Type	Thick, Thin
File-based iSCSI LUN	Tak
Block-based iSCSI LUN	Tak
Maximum LUN size	250 TB
Maximum number of targets LUN	Note: At least 4 GB RAM is required. 128
LUN feature	1. LUN Mapping (LUN can be moved between iSCSI and FC) 2. LUN Masking 3. WWPN Aliases Import/Export 4. FC Port Group 5. FC Port Binding 6. Multipath IO (MPIO) 7. Online LUN capacity expansion 8. LUN snapshot 9. LUN snapshot replication and clone
Auto Tiering	Tak
RAID Type	Requires minimum 2GB memory. 1. 8-bay (and more): JBOD, Single, RAID 0, 1, 5, 6, 10, 50, 60

	2. 6-bay: JBOD, Single, RAID 0, 1, 5, 6, 10, 50 3. 4-bay: JBOD, Single, RAID 0, 1, 5, 6, 10 4. 2-bay: JBOD, Single, RAID 0, 1
RAID Group	Tak
	To ensure data security, system stability, and storage performance, the maximum number of drives for a single RAID group is now 16 (applicable to RAID 5, RAID 6, RAID TP, and subgroups of RAID 50 and RAID 60). Nevertheless, users can combine multiple RAID groups into a large storage pool that contains more than 16 drives, using RAID 50, RAID 60, or RAID 10 as the RAID configuration. This enhancement will only be applied to new RAID groups. All existing RAID groups and storage systems will not be affected.
RAID Level Migration	Tak
RAID Expansion (by adding Disk)	Tak
RAID Expansion (by replacing bigger Disks)	Tak
Storage Pool Expansion (by adding RAID Group)	Tak
RAID Hot Spare	Global, Local
RAID Sync/Rebuild/Scrubbing	Tak
Internal drive	EXT4
External drive	EXT3, EXT4, NTFS, FAT32, HFS+, and exFAT (optional for ARM model)
	Note: To use exFat in certain models you must purchase an exFAT driver license from License Center.
Disk, Enclosure Locate	Tak
Disk S.M.A.R.T. Scan	Tak
Disk S.M.A.R.T. Data Migration	Tak
Ironwolf Health Management	Tak
Secure Erase	Tak
SSD Trim	Tak
SSD Life Estimation	Tak
Disk Roaming	Tak
Disk Standby	Tak
Volume Snapshot	Tak
LUN Snapshot	Tak
Maximum Snapshot (Per System)	Check maximum number of snapshots of your NAS
Maximum Snapshot (Per Volume / LUN)	Check maximum number of snapshots of your NAS
Minimum Snapshot Interval	5 minutes
Snapshot Retention Policy	Tak
Self-serve Snapshot Recovery	Tak
Application Consisted Snapshot	Tak
Snapshot Full Clone	Tak
Snapshot Replica / Vault	Tak
SSD read-only Cache	Tak
SSD read-write cache	Tak
SSD write-only cache	Tak
SSD Cache Maximum Size	Check your QNAP NAS cache capacity and RAM requirements
SSD Cache RAID	0, 1, 5, 6, 10
SSD profiling tool	Tak
External Device Management	Tak
Mount Smart Phone (MTP)	Tak
External RAID Device (QNAP so on) Management (External Device Mode)	Tak
External RAID Device (QNAP so on) Management (NAS Mode)	Tak
File Server	1. File sharing across Windows, Mac, and Linux/UNIX 2. Microsoft networking (CIFS/SMB) 3. Apple networking (AFP) 4. NFS version 3/4 services
FTP Server	1. QuFTP 2. FTP, SFTP and TFTP protocols 3. FTP over SSL/TLS (explicit FTPS) 4. FXP support
Maximum FTP connection	1024
File Station (Web)	Tak
Object Storage	Tak

Local user account	4,096
Local group account	512
Domain user/group account	200,000
Domain Security	Tak
Domain Controller	Tak
Shared folder permission	Tak
Advanced folder permission	Tak, (AFP, CIFS/SMB, FTP, and File Station)
Windows ACL	Tak, (CIFS/SMB)
User quota	Tak
Group quota	Tak
Folder quota	Tak, (Snapshot shared folder)
Home folder	Tak
Resource Monitor	Tak
SNMP	V2, V3
Network recycle bin	1. Recover files deleted using AFP, CIFS/SMB, and File Station 2. Automatic cleanup and file type filter
System Log & Notification Center	Log recording: 3,000 event per second
Smart Fan	Tak
Schedule on/off	Tak
Internet protocol	IPv4, IPv6
Virtual Switch	Tak
Port trunking	Tak, (7 modes)
VLAN	Tak
DHCP Server	Tak
DDNS (Dynamic Domain Name Service)	Tak
Network access protection with auto-blocking	SSH, Telnet, HTTP(S), FTP, CIFS/SMB, and AFP
Security Counselor	Tak
Malware Remover	Tak
AES 256-bit Volume Encryption validated by FIPS 140-2 CAVP	Tak
2-step verification	Tak
Allow/Deny List	Tak
Access Protection	Tak
Service binding	Tak
Firewall	Tak
vSphere Web Client Plug-in	Tak
VMware vSphere VAAI for iSCSI	Tak
VMware vSphere VAAI for NAS	Tak
Windows ODX	Tak
Windows/VMware Snapshot Agent	Tak
HTTP/HTTPS Connections	TLS 1.0/1.1/1.2/1.3
Supports WebDAV Connection	Tak
Supports Virtual Hosts	32
Qsync	Tak
[Qsync] Management Mode	Note: At least 1 GB RAM is required.
[Qsync] Qsync client supported platforms	User customization, Central
[Qsync] Maximum number of version control	Windows, macOS, Ubuntu, Android, and iOS
HybridMount	64
	Tak
	Note: At least 1 GB RAM is required.
[HybridMount] File Cloud Gateway	Concurrent Connections = 20 Upload & 20 Download
[HybridMount] Network Drive Mount	Tak
[HybridMount] Free cloud gateway sessions	2
HBS (Hybrid Backup Sync)	Tak
	Note: At least 1 GB RAM is required.
[HBS (Hybrid Backup Sync)] NAS to NAS backup	Tak
[HBS (Hybrid Backup Sync)] Cloud Backup	Tak
[HBS (Hybrid Backup Sync)] Cloud Sync	Tak
[HBS (Hybrid Backup Sync)] 2-way and Active Sync	Tak
[HBS (Hybrid Backup Sync)] Apple Time Machine Backup	Tak

[HBS (Hybrid Backup Sync)] External drive backup	Tak
[HBS (Hybrid Backup Sync)] Maximum number of backup job	400
Boxafe	Tak
	Note: At least 4 GB RAM is required.
[Boxafe] Office 365 Backup	Tak
[Boxafe] Google Workspace Backup	Tak
[Boxafe] Full-text search	Tak
Qsirch	Tak
	Note: This feature is supported by all QNAP NAS devices with at least 2 GB of memory
[Qsirch] Previews	Photos, music, videos, PDFs, Gmail, and others
[Qsirch] Integrate Mac Finder	Tak
[Qsirch] Advanced picture search	Tak
[Qsirch] Search filters	Tak
QuMagie	Tak
	Note: At least 1 GB RAM is required.
[QuMagie] Browse photos	Tak
[QuMagie] Virtual and smart albums	Tak
[QuMagie] AI-assisted photo management	People, things, places, and others
Antivirus (free)	Tak
QVPN Service	Tak
	Note: At least 1 GB RAM is required.
[QVPN Service] Remote Access	PPTP, L2TP/IPSec, OpenVPN, WireGuard, QBelt (QNAP proprietary)
[QVPN Service] Supported utility and mobile app	Windows, macOS, iOS, and Android
[QVPN Service] Supported maximum clients	100
LDAP Server	Tak
RADIUS	Tak
SQL server	Tak
License Center	Tak
Multimedia Console	Tak
Photo Station	Tak
Music Station	Tak
Video Station	Tak
Download Station	Tak
Notes Station	Tak
Qfiling	Tak
Media Streaming add-on	Tak
QmailAgent	Tak
QuWAN	Tak
DA Driver Analyzer	Tak
Q'center	Tak
	Note: The application is available in the App Center and in virtual appliance marketplaces (VMware vSphere ESXi and Microsoft Hyper-V).
Q'center Server	Tak
Q'center Agent	Tak
Connect to Q'center	Tak
Container Station	Tak
	Note: At least 1 GB RAM is required.
[Container Station] Supported type	LXC/LXD and Docker
	Note: LXD has been supported after Container Station 2.4
[Container Station] Docker Hub Registry	Tak
[Container Station] Container importing and exporting	Tak
[Container Station] Console mode	Tak
QVR Pro	Tak

Note: At least 4 GB RAM is required. The maximum number of

[QVR Pro] Recording Technique	channels supported varies by NAS model, network configuration, and camera settings. For more information, visit https://www.qnap.com/go/qvr-nas-selector .
[QVR Pro] License Type	Index database based
[QVR Pro] User-defined trigger events	Perpetual
[QVR Pro] Metadata	Tak
[QVR Pro] QVR Pro Client (Desktop)	Tak
[QVR Pro] QVR Pro Client (Mobile)	Windows, macOS, and QNAP HybridDesk Station
[QVR Pro] Recording camera streams	Android and iOS
[QVR Pro] Free built-in camera channels	H.264
QVR Elite	8
	Tak
Note: At least 1 GB RAM is required. The maximum number of channels supported varies by NAS model, network configuration, and camera settings. For more information, visit https://www.qnap.com/go/qvr-nas-selector .	
[QVR Elite] Recording Technique	Standard MP4 file based
[QVR Elite] License Type	Subscription-based
[QVR Elite] User-defined trigger events	Tak
[QVR Elite] QVR Pro Client (Desktop)	Windows, macOS, and QNAP HybridDesk Station
[QVR Elite] QVR Pro Client (Mobile)	Android and iOS
[QVR Elite] Recording camera streams	H.264
[QVR Elite] Free built-in camera channels	2
QVR Pro Client	Tak
[QVR Pro Client] Dynamic View Layout	Tak
[QVR Pro Client] Windows	Tak
[QVR Pro Client] Mac	Tak
[QVR Pro Client] HybridDesktop	Tak
[QVR Pro Client] iOS	Tak
[QVR Pro Client] Android	Tak
QVR Human	Tak
QVR Face	Tak
The maximum number of channels supported varies by NAS model, network configuration, and camera settings. For more information, visit https://www.qnap.com/solution/qvr-face/en-us/	
QVR DoorAccess	Tak

Zawartość opakowania

TS-432X
 Kabel Ethernet x 1
 Zasilacz sieciowy x 1
 Przewód zasilający x 1
 Śruba z łbem płaskim x 16 (dla dysku twardego 3,5 cala)
 Śruba z łbem płaskim x 12 (dla dysku twardego 2,5 cala)
 Skrócona instrukcja instalacji (QIG)