

Link do produktu: <https://sklepqnap.pl/serwer-qnap-tvs-h877ax-r5-16g-p-3364.html>

Serwer QNAP TVS-h877AX-R5-16G

Cena	19 357,38 zł
Dostępność	Na zamówienie
Numer katalogowy	QNA_TVSh877AXR516G
Kod producenta	TVS-h877AX-R5-16G
Kod EAN	4711103091715
Producent	QNAP
Pamięć RAM	16GB
Port 2,5 GbE	2

Opis produktu



QNAP TVS-h877AX-R5-16G

QNAP TVS-h877AX-R5-16G to zaawansowany, 8-zatokowy **serwer NAS stworzony dla firm, profesjonalistów oraz wymagających środowisk wirtualizacji i pracy z dużymi zbiorami danych**. Wyposażony w AMD Ryzen 5 serii 7000, 16 GB DDR5, 6 zatok SATA oraz 2 gniazda U.2 NVMe Gen4, łączy dużą pojemność z bardzo wysoką wydajnością. Dwa porty 10GbE, dwa 2,5GbE oraz trzy gniazda PCIe Gen4 zapewniają szerokie możliwości rozbudowy infrastruktury

Cechy wyjątkowe dysku sieciowego **QNAP TVS-h877AX**:

AMD Ryzen 5 7000 – 6 rdzeni / 12 wątków i taktowanie do 5,1 GHz.

16 GB DDR5 – szybka pamięć z możliwością rozbudowy aż do 192 GB; obsługiwane są również opcjonalne moduły ECC.

8 zatok w konfiguracji hybrydowej – 6 × SATA 3,5" + 2 × U.2 NVMe Gen4 x2, pozwalające połączyć dużą pojemność HDD z wydajnością SSD.

2 × 10GbE – szybka transmisja danych idealna do dużych plików, backupu i pracy wielostanowiskowej.

2 × 2,5GbE – dodatkowe interfejsy sieciowe zwiększające elastyczność konfiguracji.

3 × PCIe Gen4 – możliwość instalacji kart sieciowych, rozszerzeń pamięci masowej czy kompatybilnych kart GPU.

NFS over RDMA – technologia zaprojektowana z myślą o wysokiej przepustowości i niskich opóźnieniach, szczególnie przydatna w zastosowaniach AI.

QuTS hero i system plików ZFS – zaawansowana ochrona integralności danych, migawki, samonaprawianie oraz funkcje klasy enterprise.

Wirtualizacja i kontenery – możliwość uruchamiania maszyn wirtualnych i kontenerów oraz wykorzystania NAS jako centralnej platformy dla aplikacji biznesowych.

Qtier – możliwość automatycznego wykorzystania różnych poziomów pamięci masowej w celu optymalizacji wydajności i pojemności.

Duża skalowalność – możliwość dalszej rozbudowy sieci i funkcjonalności dzięki gniazdom PCIe.

Szyfrowanie AES-NI – sprzętowe wsparcie dla operacji szyfrowania danych.

Konstrukcja Tower – duża liczba zatok przy zachowaniu formy odpowiedniej do instalacji w biurze lub serwerowni.

5-letnia gwarancja – producent oferuje dla tego modelu standardową 5-letnią gwarancję.

Podstawowe funkcje **dysku sieciowego QNAP**:

Dostęp do danych w domu oraz z dowolnego miejsca na świecie.



System QNAP zapewnia szybki, a przede wszystkim bezpieczny sposób na udostępnianie danych każdemu i wszędzie. Dzięki aplikacji File Station oraz wbudowanemu **serwerowi VPN** można przeszukiwać, organizować i przenosić pliki pomiędzy QNAP, a dowolnym urządzeniem w sieci. Udostępnianie plików dla każdej platformy Windows, MAC czy Linux.

Możliwość rozbudowy PCIe Gen 4 dla przyszłościowych modernizacji

Model TVS-h877AX posiada 3 gniazda PCIe Gen 4, zapewniając elastyczną rozbudowę sprzętową, aby sprostać rosnącym potrzebom biznesowym. Zainstaluj karty sieciowe 25GbE dla wyższej przepustowości lub dodaj karty graficzne NVIDIA RTX™ serii 4000/5000, aby zwiększyć możliwości obliczeń AI i przetwarzania wideo.

Połącz prędkość U.2 NVMe z pojemnością Dysk twardy. Nadchodzi Qtier

Maksymalizuj wydajność pamięci masowej bez kompromisów. TVS-h877AX posiada hybrydowe zatoki obsługujące zarówno U.2 NVMe SSD, jak i tradycyjne dyski HDD, co pozwala połączyć szybkość NVMe z pojemnością twardych dysków.

AMD Ryzen™ 7000 i DDR5: przesuwanie granic wielozadaniowości

Dzięki najnowszej architekturze Zen 4 TVS-h877AX zapewnia znaczący wzrost IPC. W połączeniu z pamięcią DDR5 (rozszerzalną do 192 GB) bez wysiłku obsługuje wymagające obciążenia, w tym wiele maszyn wirtualnych (VM), kontenerów i transkodowanie wideo w wysokiej rozdzielczości.

Zbuduj inteligentne centrum wiedzy z wyszukiwania RAG

TVS-h877AX integruje silnik wyszukiwania Qsirsch z technologią RAG, chmurowymi dużymi modelami językowymi (LLM) oraz generatywną sztuczną inteligencją. Pozwala to na precyzyjne wyszukiwanie w języku naturalnym wśród ogromnej zawartości plików na serwerze NAS oraz generowanie podsumowań i praktycznych informacji.

Zabezpieczenie danych NetBak PC Agent.

NetBak PC Agent **zapewnia tworzenie kopii zapasowych systemu** i pełne przywracanie urządzeń dla aplikacji, ustawień systemowych i danych z komputerów PC i serwerów Windows®. Możesz łatwo połączyć swojego klienta Windows z QNAP NAS za pomocą zaledwie kilku kliknięć i tworzyć zadania tworzenia kopii zapasowych. NetBak PC Agent **obsługuje również przywracanie bez wyłączania**, co zapewnia większą elastyczność użytkownika.



Specyfikacja sprzętowa

Procesor	Procesor AMD Ryzen™ 5 serii 7000 6-rdzeniowy/12-wątkowy, zwiększenie taktowania do 5,1 GHz
	Grafika AMD Radeon
	Architektura procesora
	Procesory graficzne
	Mechanizm szyfrowania
	Transkodowanie wspomaganie sprzętowo
	Pamięć systemowa
	Maksymalna pojemność pamięci
	Gniazdo pamięci
	16 GB UDIMM DDR5
	192 GB (4 x 48 GB)
	4 x UDIMM DDR5
	Wspiera opcjonalną pamięć ECC
	Dla konfiguracji z dwoma modułami DIMM, musisz użyć par identycznych modułów DDR5.
	5GB (Ochrona podwójnego uruchamiania systemu operacyjnego)
Pamięć flash	5GB (Ochrona podwójnego uruchamiania systemu operacyjnego)
Wnęka dysk	6 x 3,5-calowy SATA 6Gb/s, 3Gb/s + 2 x 2,5-calowy U.2 NVMe Ge4 x4 gniazda
Kompatybilność dysk	Zatoki 3,5-calowe: 3,5-calowy dysk SATA twarde dyski 2,5-calowy dysk SSD SATA twarde dyski
	Zatoki 2,5-calowe: 2,5-calowy dysk SSD U.2 twarde dyski Dyski SSD U.2 NVMe są kompatybilne tylko z dyskami SSD PCIe Gen 4 i PCIe Gen 5 . Aby włączyć funkcję hot-swap dla dysków U.2 SSD po uruchomieniu systemu, dysk U.2 SSD musi być zainstalowa przed włączeniem zasilania systemu.
Wymieniany podczas pracy	Tak
Obsługa przyspieszenia Pamięć podręczna SSD	Tak
GPU pass-through	Tak
Port 2,5 Gigabit Ethernet (2,5G/1G/100M)	2(2,5G/1G/100M/10M)
Port 10 Gigabit sieci Ethernet	2 x 10GBASE-T (10G/5G/2,5G/1G/100M)
Port 25 Gigabit Ethernet	Opcjonalne przez kartę
Wake on LAN (WOL)	Tak
Ramka Jumbo	Tak
Gniazdo PCIe	3
	Slot 1: Gen 4 x 8 lub Gen 4 x 4*
	Slot 2: Gen 4 x 4
	Slot 3: Gen 4 x 4
	*Slot 1 zapewnia szerokość PCIe Gen 4 x8, gdy Slot 2 nie jest używany, oraz szerokość PCIe Gen 4 x4, gdy Slot 2 jest używany.
	Wymiary karty dla slotu PCIe 1: 268 x 112 x 40,64 (podwójny slot) mm / 10,5 x 4,4 x 1,6 cala
	Wymiary karty dla slotu PCIe 2: 250 x 68,9 x 18,76 mm / 9,8 x 2,71 x 0,74 cala
	Wymiary karty dla slotu PCIe 3: 250 x 68,9 x 18,76 mm / 9,8 x 2,71 x 0,74 cala

	x 2,71 x 0,74 cala
	Szersze karty mogą być zainstalowane, jeśli kolejny slot PC nie będzie używany.
Port USB 2.0	2
Port USB 3.2 Gen 2 (10 Gb/s)	2 x typu C USB 3.2 Gen 2 10 Gb/s
Wyjście HDMI™	1, HDMI™ 1.4b (up to 4096 x 2160 @ 30Hz)
Kształt	Tower
Wskaźniki LED	Status zasilania, HDD 1-6, U.2 SSD 1-2, Status, LAN, status portu rozszerzenia pamięci
Przyciski	Zasilanie, reset, automatyczne kopiowanie USB
Wymiary (wys. x szer. x gł.)	225 x 292,9 x 319,8 mm
Waga netto	8.88 kg
Waga (brutto)	11.2 kg
Temperatura robocza	0-40°C
Temperatura Pamięć masowa	-20-70°C
Wilgotność względna	5-95% bez kondensacji, temperatura mokrego termometru
	27°C
Zasilacz	500W(x1), 100-240V
	1 x 8 (6+2)-pinowy kabel PCI-e
Pobór mocy: tryb pracy, typowy	105.12 W
	Testy wykonane przy całkowicie zapełnionych dyskach.
Wentylator	Wentylator systemowy: 2 x 80mm, 12VDC
	Wentylator CPU: 2 x 60 mm, 12V DC
Ostrzeżenie systemowe	Brzęczyk
Standardowa gwarancja	5 years

Specyfikacja oprogramowania

Operating System	QTS 5.2.9
Supported Client Operating Systems	1. Apple Mac OS 10.10 or later 2. Ubuntu 14.04, CentOS 7, RHEL 6.6, SUSE 12 or later Linux 3. IBM AIX 7, Solaris 10 or later UNIX 4. Microsoft Windows 7, 8, 10 and 11 5. Microsoft Windows Server 2008 R2, 2012, 2012 R2, 2016, 2019 and 2022
Supported Browsers	1. Apple Safari (latest version) 2. Google Chrome (latest version) 3. Microsoft Edge (latest version) 4. Mozilla Firefox (latest version)
Supported Languages	Chinese (Traditional & Simplified), Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese (Brazil), Romanian, Russian, Spanish, Swedish, Thai, and Turkish
Storage Pool	Tak
SED Storage Pool	Tak
Maximum Pool size	308 TB
Maximum number of storage pool	128
Volume Type	Thick, Thin, Static
Maximum volume size	250 TB
Maximum number of volume	Note: At least 4 GB RAM is required. 128
Maximum shared folder size	250 TB
Maximum number of shared folder	512
JBOD Expansion	Tak
VJBOD / VJBOD Cloud	Tak
iSCSI Service	Tak
Fibre Channel Service	Tak
LUN Type	Thick, Thin
File-based iSCSI LUN	Tak
Block-based iSCSI LUN	Tak
Maximum LUN size	250 TB

Maximum number of targets LUN	Note: At least 4 GB RAM is required.
LUN feature	128
	1. LUN Mapping (LUN can be moved between iSCSI and FC) 2. LUN Masking 3. WWPN Aliases Import/Export 4. FC Port Group
Auto Tiering	Tak
RAID Type	Requires minimum 2GB memory. 1. 8-bay (and more): JBOD, Single, RAID 0, 1, 5, 6, 10, 50, 60 2. 6-bay: JBOD, Single, RAID 0, 1, 5, 6, 10, 50 3. 4-bay: JBOD, Single, RAID 0, 1, 5, 6, 10 4. 2-bay: JBOD, Single, RAID 0, 1
RAID Group	Tak
	To ensure data security, system stability, and storage performance, the maximum number of drives for a single RAID group is now 16 (applicable to RAID 5, RAID 6, RAID TP, and subgroups of RAID 50 and RAID 60). Nevertheless, users can combine multiple RAID groups into a large storage pool that contains more than 16 drives, using RAID 50, RAID 60, or RAID 10 as the RAID configuration. This enhancement will only be applied to new RAID groups. All existing RAID groups and storage systems will not be affected.
RAID Level Migration	Tak
RAID Expansion (by adding Disk)	Tak
RAID Expansion (by replacing bigger Disks)	Tak
Storage Pool Expansion (by adding RAID Group)	Tak
RAID Hot Spare	Global, Local
RAID Sync/Rebuild/Scrubbing	Tak
Internal drive	EXT4
External drive	EXT3, EXT4, NTFS, FAT32, HFS+, and exFAT (optional for ARM model)
	Note: To use exFat in certain models you must purchase an exFAT driver license from License Center.
Disk, Enclosure Locate	Tak
Disk S.M.A.R.T. Scan	Tak
Disk S.M.A.R.T. Data Migration	Tak
Ironwolf Health Management	Tak
Secure Erase	Tak
SSD Trim	Tak
SSD Life Estimation	Tak
Disk Roaming	Tak
Disk Standby	Tak
Volume Snapshot	Tak
LUN Snapshot	Tak
Maximum Snapshot (Per System)	Check maximum number of snapshots of your NAS
Maximum Snapshot (Per Volume / LUN)	Check maximum number of snapshots of your NAS
Minimum Snapshot Interval	5 minutes
Snapshot Retention Policy	Tak
Self-serve Snapshot Recovery	Tak
Application Consisted Snapshot	Tak
Snapshot Full Clone	Tak
Snapshot Replica / Vault	Tak
SSD read-only Cache	Tak
SSD read-write cache	Tak
SSD write-only cache	Tak
SSD Cache Maximum Size	Check your QNAP NAS cache capacity and RAM requirements
SSD Cache RAID	0, 1, 5, 6, 10
SSD profiling tool	Tak
External Device Management	Tak
Mount Smart Phone (MTP)	Tak
External RAID Device (QNAP so on)	Tak

Management (External Device Mode)	
External RAID Device (QNAP so on)	Tak
Management (NAS Mode)	
File Server	1. File sharing across Windows, Mac, and Linux/UNIX 2. Microsoft networking (CIFS/SMB) 3. Apple networking (AFP) 4. NFS version 3/4 services
FTP Server	1. QuFTP 2. FTP, SFTP and TFTP protocols 3. FTP over SSL/TLS (explicit FTPS) 4. FXP support
Maximum FTP connection	1024
File Station (Web)	Tak
Object Storage	Tak
Local user account	4,096
Local group account	512
Domain user/group account	200,000
Domain Security	Tak
Domain Controller	Tak
Shared folder permission	Tak
Advanced folder permission	Tak, (AFP, CIFS/SMB, FTP, and File Station)
Windows ACL	Tak, (CIFS/SMB)
User quota	Tak
Group quota	Tak
Folder quota	Tak, (Snapshot shared folder)
Home folder	Tak
Resource Monitor	Tak
SNMP	V2, V3
Network recycle bin	1. Recover files deleted using AFP, CIFS/SMB, and File Station 2. Automatic cleanup and file type filter
System Log & Notification Center	Log recording: 3,000 event per second
Smart Fan	Tak
Schedule on/off	Tak
Internet protocol	IPv4, IPv6
Virtual Switch	Tak
Port trunking	Tak, (7 modes)
VLAN	Tak
DHCP Server	Tak
DDNS (Dynamic Domain Name Service)	Tak
Network access protection with auto-blocking	SSH, Telnet, HTTP(S), FTP, CIFS/SMB, and AFP
Security Counselor	Tak
Malware Remover	Tak
AES 256-bit Volume Encryption validated by FIPS 140-2 CAVP	Tak
2-step verification	Tak
Allow/Deny List	Tak
Access Protection	Tak
Service binding	Tak
Firewall	Tak
vSphere Web Client Plug-in	Tak
VMware vSphere VAAI for iSCSI	Tak
VMware vSphere VAAI for NAS	Tak
Windows ODX	Tak
Windows/VMware Snapshot Agent	Tak
HTTP/HTTPS Connections	TLS 1.0/1.1/1.2/1.3
Supports WebDAV Connection	Tak
Supports Virtual Hosts	32
Qsync	Tak
[Qsync] Management Mode	Note: At least 1 GB RAM is required.
[Qsync] Qsync client supported platforms	User customization, Central
[Qsync] Maximum number of version control	Windows, macOS, Ubuntu, Android, and iOS
HybridMount	64
	Tak

Note: At least 1 GB RAM is required.

[HybridMount] File Cloud Gateway	Concurrent Connections = 20 Upload & 20 Download
[HybridMount] Network Drive Mount	Tak
[HybridMount] Free cloud gateway sessions	2
HBS (Hybrid Backup Sync)	Tak
Note: At least 1 GB RAM is required.	
[HBS (Hybrid Backup Sync)] NAS to NAS backup	Tak
[HBS (Hybrid Backup Sync)] Cloud Backup	Tak
[HBS (Hybrid Backup Sync)] Cloud Sync	Tak
[HBS (Hybrid Backup Sync)] 2-way and Active Sync	Tak
[HBS (Hybrid Backup Sync)] Backup Deduplication	Tak
[HBS (Hybrid Backup Sync)] Apple Time Machine Backup	Tak
[HBS (Hybrid Backup Sync)] External drive backup	Tak
[HBS (Hybrid Backup Sync)] Maximum number of backup job	400
Hyper Data Protector	Tak
Boxafe	Tak
Note: At least 4 GB RAM is required.	
[Boxafe] Office 365 Backup	Tak
[Boxafe] Google Workspace Backup	Tak
[Boxafe] Full-text search	Tak
Qsirch	Tak
Note: This feature is supported by all QNAP NAS devices with at least 2 GB of memory	
[Qsirch] Previews	Photos, music, videos, PDFs, Gmail, and others
[Qsirch] Integrate Mac Finder	Tak
[Qsirch] Advanced picture search	Tak
[Qsirch] Search filters	Tak
QuMagie	Tak
Note: At least 1 GB RAM is required.	
[QuMagie] Browse photos	Tak
[QuMagie] Virtual and smart albums	Tak
[QuMagie] AI-assisted photo management	People, things, places, and others
Antivirus (free)	Tak
McAfee (License)	Tak
QVPN Service	Tak
Note: At least 1 GB RAM is required.	
[QVPN Service] Remote Access	PPTP, L2TP/IPSec, OpenVPN, WireGuard, QBelt (QNAP proprietary)
[QVPN Service] Supported utility and mobile app	Windows, macOS, iOS, and Android
[QVPN Service] Supported maximum clients	100
LDAP Server	Tak
RADIUS	Tak
SQL server	Tak
License Center	Tak
Multimedia Console	Tak
Photo Station	Tak
Music Station	Tak
Video Station	Tak
Download Station	Tak
Notes Station	Tak
Qfiling	Tak
Media Streaming add-on	Tak
QmailAgent	Tak
QuWAN	Tak
DA Driver Analyzer	Tak
Q'center	Tak
Note: The application is available in the App Center and in	

Q'center Server	virtual appliance marketplaces (VMware vSphere ESXi and Microsoft Hyper-V).
Q'center Agent	Tak
Connect to Q'center	Tak
Virtualization Station	Tak
[Virtualization Station] Supports Virtual machine instances	Note: At least 4 GB RAM is required. Windows, Linux, Unix, and Android
[Virtualization Station] VM importing, exporting, cloning, snapshot capturing, backup, and restoration	All function is Fine.
[Virtualization Station] Virtual switches	Can create a virtual switch
[Virtualization Station] GPU pass-through	Not support GPU
[Virtualization Station] Suggested number of virtual machine instances	12
Container Station	The actual number of virtual machine instances may vary by the memory installed on NAS (e.g. 1 VM= 1 thread for 1 vCPU and 1GB memory). Please expend memory if needed. Tak
[Container Station] Supported type	Note: At least 1 GB RAM is required. LXC/LXD and Docker
[Container Station] Docker Hub Registry	Note: LXD has been supported after Container Station 2.4 Tak
[Container Station] Container importing and exporting	Tak
[Container Station] Console mode	Tak
Linux Station	Tak
[Linux Station] Supports Ubuntu versions	Notification: At least 4 GB RAM is required. 18.04, and 20.04
Linux Station Center	Tak
QVR Pro	Tak
[QVR Pro] Recording Technique	Note: At least 4 GB RAM is required. The maximum number of channels supported varies by NAS model, network configuration, and camera settings. For more information, visit https://www.qnap.com/go/qvr-nas-selector .
[QVR Pro] License Type	Index database based
[QVR Pro] User-defined trigger events	Perpetual
[QVR Pro] Metadata	Tak
[QVR Pro] QVR Pro Client (Desktop)	Tak
[QVR Pro] QVR Pro Client (Mobile)	Windows, macOS, and QNAP HybridDesk Station
[QVR Pro] Recording camera streams	Android and iOS
[QVR Pro] Free built-in camera channels	H.264
QVR Elite	8
[QVR Elite] Recording Technique	Tak
[QVR Elite] License Type	Note: At least 1 GB RAM is required. The maximum number of channels supported varies by NAS model, network configuration, and camera settings. For more information, visit https://www.qnap.com/go/qvr-nas-selector .
[QVR Elite] User-defined trigger events	Standard MP4 file based
[QVR Elite] QVR Pro Client (Desktop)	Subscription-based
[QVR Elite] QVR Pro Client (Mobile)	Tak
[QVR Elite] Recording camera streams	Windows, macOS, and QNAP HybridDesk Station
[QVR Elite] Free built-in camera channels	Android and iOS
QVR Pro Client	H.264
[QVR Pro Client] Dynamic View Layout	2
[QVR Pro Client] Windows	Tak
[QVR Pro Client] Mac	Tak
[QVR Pro Client] HybridDesktop	Tak
[QVR Pro Client] iOS	Tak
[QVR Pro Client] Android	Tak

QVR Center	Tak
[QVR Center] Log management	Note: At least 4 GB RAM is required. Tak
[QVR Center] Central monitoring across multiple servers	Tak
QVR Guard	Tak
[QVR Guard] Failover design	Note: At least 4 GB RAM is required. Tak
[QVR Guard] Viewing task details	Tak
[QVR Guard] Automatic switch between Standby and Takeover modes	Tak
QVR Human	Tak
QVR Face	Tak
QVR DoorAccess Operating System Supported Client Operating Systems	The maximum number of channels supported varies by NAS model, network configuration, and camera settings. For more information, visit https://www.qnap.com/solution/qvr-face/en-us/ Tak QuTS hero h5.2.9
Supported Browsers	1. Apple Mac OS 10.10 or later 2. Ubuntu 14.04, CentOS 7, RHEL 6.6, SUSE 12 or later Linux 3. IBM AIX 7, Solaris 10 or later UNIX 4. Microsoft Windows 7, 8, 10, and 11 1. Apple Safari (latest version) 2. Google Chrome (latest version) 3. Microsoft Edge (latest version) 4. Mozilla Firefox (latest version)
Supported Languages	Chinese (Traditional & Simplified), Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese (Brazil), Romanian, Russian, Spanish, Swedish, Thai, and Turkish
Storage Pool	Tak
SED Storage Pool	Tak
Maximum Pool size	5 PB
Maximum number of storage pool	128
Shared Folder Type	Thick, Thin
Maximum shared folder size	5 PB
Maximum number of shared folder	256
JBOD Expansion	Tak
VJBOD / VJBOD Cloud	Tak
iSCSI Service	Tak
Fibre Channel Service	Tak
LUN Type	Thick, Thin
Block-based iSCSI LUN	Tak
Maximum LUN size	1024 TB
Maximum number of targets LUN	256
RAID Type	1. 8-bay (and more): Single, RAID 0 (Stripe), 1, 5, 6, 10, 50, 60, Triple Mirror, Triple Parity 2. 6-bay: Single, RAID 0 (Stripe), 1, 5, 6, 10, 50, Triple Mirror, Triple Parity 3. 4-bay: Single, RAID 0 (Stripe), 1, 5, 6, 10, Triple Mirror, Triple Parity 4. 3-bay: Single, RAID 0 (Stripe), 1, 5, Triple Mirror, Triple Parity
RAID Group	To ensure data security, system stability, and storage performance, the maximum number of drives for a single RAID group is now 16 (applicable to RAID 5, RAID 6, RAID TP, and subgroups of RAID 50 and RAID 60). Nevertheless, users can combine multiple RAID groups into a large storage pool that

	contains more than 16 drives, using RAID 50, RAID 60, or RAID 10 as the RAID configuration. This enhancement will only be applied to new RAID groups. All existing RAID groups and storage systems will not be affected.
RAID Expansion (by replacing bigger Disks)	Tak
Storage Pool Expansion (by adding RAID Group)	Tak
RAID Hot Spare	Global, Local
RAID Sync/Rebuild/Scrubbing	Tak
End-to-End data integrity	Tak
Silent error detection and self-healing	Tak
Internal drive	ZFS
External drive	EXT3, EXT4, NTFS, FAT32, HFS+, and exFAT
Disk, Enclosure Locate	Tak
Disk S.M.A.R.T. Scan	Tak
Disk S.M.A.R.T. Data Migration	Tak
Ironwolf Health Management	Tak
Secure Erase	Tak
SSD Trim	Tak
SSD Life Estimation	Tak
Disk Roaming	Tak
Disk Standby	Tak
Shared Folder Snapshot	Tak
LUN Snapshot	Tak
Maximum Snapshot (Per System)	Check maximum number of snapshots of your NAS
Maximum Snapshot (Per Volume / LUN)	Check maximum number of snapshots of your NAS
Minimum Snapshot Interval	1 minute
Snapshot Retention Policy	Tak
Self-serve Snapshot Recovery	Tak
Application Consisted Snapshot	Tak
Snapshot Full Clone	Tak
Snapshot Instant Clone	Tak
Snapshot Replica / Vault	Tak
SSD read-only Cache	Tak
SSD read & write log cache	Tak
SSD dedicated ZIL cache	Tak
SSD Cache Maximum Size	Check your QNAP NAS cache capacity and RAM requirements
SSD Cache RAID	0, 1, 10 (journal)
External Device Management	Tak
Mount Smart Phone (MTP)	Tak
External RAID Device (QNAP so on) Management (External Device Mode)	Tak
External RAID Device (QNAP so on) Management (NAS Mode)	Tak
File Server	1. File sharing across Windows, Mac, and Linux/UNIX 2. Microsoft networking (CIFS/SMB) 3. Apple networking (AFP) 4. NFS version 2/3/4/4.1 services
FTP Server	1. FTP, SFTP and TFTP protocols 2. FTP over SSL/TLS (explicit FTPS) 3. FXP support
Maximum FTP connection	1024
Shared Folder Data Compression	Tak
Shared Folder Data Deduplication	Tak
Shared Folder WORM	Tak
File Station (Web)	Tak
Object Storage	Tak
Local user account	16,000
Local group account	512
Domain user/group account	200,000
Domain Security	Tak
Domain Controller	Tak
Shared folder permission	Tak
Windows ACL	Tak
User quota	Tak
Group quota	Tak
Folder quota	Tak
Home folder	Tak
Resource Monitor	Tak

SNMP	V2, V3
Network recycle bin	1. Recover files deleted using AFP, CIFS/SMB, and File Station 2. Automatic cleanup and file type filter
System Log & Notification Center	Log recording: 3,000 event per second
Smart Fan	Tak
Schedule on/off	Tak
Internet protocol	IPv4, IPv6
Virtual Switch	Tak
Port trunking	Tak, (7 modes)
VLAN	Tak
DHCP Server	Tak
DDNS (Dynamic Domain Name Service)	Tak
Network access protection with auto-blocking	SSH, Telnet, HTTP(S), FTP, CIFS/SMB, and AFP
Security Counselor	Tak
Malware Remover	Tak
AES 256-bit Folder Encryption validated by FIPS 140-2 CAVP	Tak
2-step verification	Tak
Allow/Deny List	Tak
Access Protection	Tak
Service binding	Tak
Firewall	Tak
vSphere Web Client Plug-in	Tak
VMware vSphere VAAI for iSCSI	Tak
VMware vSphere VAAI for NAS	Tak
Windows ODX	Tak
Windows/VMware Snapshot Agent	Tak
HTTP/HTTPS Connections	TLS 1.0/1.1/1.2/1.3
Supports WebDAV Connection	Tak
Supports Virtual Hosts	32
Qsync	Tak
[Qsync] Management Mode	Note: At least 1 GB RAM is required.
[Qsync] Qsync client supported platforms	User customization, Central
[Qsync] Maximum number of version control	Windows, macOS, Ubuntu, Android, and iOS
HybridMount	64
[HybridMount] File Cloud Gateway	Note: At least 1 GB RAM is required.
[HybridMount] Network Drive Mount	Concurrent Connections = 80 Upload & 80 Download
[HybridMount] Free cloud gateway sessions	Tak
HBS (Hybrid Backup Sync)	2
[HBS (Hybrid Backup Sync)] NAS to NAS backup	Note: At least 1 GB RAM is required.
[HBS (Hybrid Backup Sync)] Cloud Backup	Tak
[HBS (Hybrid Backup Sync)] Cloud Sync	Tak
[HBS (Hybrid Backup Sync)] 2-way and Active Sync	Tak
[HBS (Hybrid Backup Sync)] Backup Deduplication	Tak
[HBS (Hybrid Backup Sync)] Apple Time Machine Backup	Tak
[HBS (Hybrid Backup Sync)] External drive backup	Tak
[HBS (Hybrid Backup Sync)] Maximum number of backup job	400
Hyper Data Protector	Tak
Boxafe	Tak
[Boxafe] Office 365 Backup	Note: At least 4 GB RAM is required.
[Boxafe] Google Workspace Backup	Tak
[Boxafe] Full-text search	Tak

Qsirch	Tak
	Note: This feature is supported by all QNAP NAS devices with at least 2 GB of memory
[Qsirch] Previews	Photos, music, videos, PDFs, Gmail, and others
[Qsirch] Integrate Mac Finder	Tak
[Qsirch] Advanced picture search	Tak
[Qsirch] Search filters	Tak
QuMagie	Tak
	Note: At least 1 GB RAM is required.
[QuMagie] Browse photos	Tak
[QuMagie] Virtual and smart albums	Tak
[QuMagie] AI-assisted photo management	People, things, places, and others
Antivirus (free)	Tak
McAfee (License)	Tak
QVPN Service	Tak
	Note: At least 1 GB RAM is required.
[QVPN Service] Remote Access	PPTP, L2TP/IPSec, OpenVPN, QBelt (QNAP proprietary)
[QVPN Service] Supported utility and mobile app	Windows, macOS, iOS, and Android
[QVPN Service] Supported maximum clients	100
LDAP Server	Tak
RADIUS	Tak
SQL server	Tak
License Center	Tak
Multimedia Console	Tak
Photo Station	Tak
Music Station	Tak
Video Station	Tak
Download Station	Tak
Notes Station	Tak
Qfiling	Tak
Media Streaming add-on	Tak
QmailAgent	Tak
QuWAN	Tak
DA Driver Analyzer	Tak
Q'center	Tak
	Note: The application is available in the App Center and in virtual appliance marketplaces (VMware vSphere ESXi and Microsoft Hyper-V).
Q'center Server	Tak
Q'center Agent	Tak
Connect to Q'center	Tak
Virtualization Station	Tak
	Note: At least 4 GB RAM is required.
[Virtualization Station] Supports Virtual machine instances	Windows, Linux, Unix, and Android
[Virtualization Station] VM importing, exporting, cloning, snapshot capturing, backup, and restoration	All function is Fine.
[Virtualization Station] Virtual switches	Can create a virtual switch
[Virtualization Station] GPU pass-through	GPU function is fine
[Virtualization Station] Suggested number of virtual machine instances	16
	The actual number of virtual machine instances may vary by the memory installed on NAS (e.g. 1 VM= 1 thread for 1 vCPU and 1GB memory). Please expend memory if needed.
Container Station	Tak
	Note: At least 1 GB RAM is required.
[Container Station] Supported type	LXC/LXD and Docker
	Note: LXD has been supported after Container Station 2.4
[Container Station] Docker Hub Registry	Tak
[Container Station] Container importing and	Tak

exporting	
[Container Station] Console mode	Tak
Linux Station	Tak
[Linux Station] Supports Ubuntu versions	Notification: At least 4 GB RAM is required. 16.04, 18.04, and 20.04
Linux Station Center	Tak
QVR Elite	Tak
[QVR Elite] Recording Technique	Note: At least 1 GB RAM is required. The maximum number of channels supported varies by NAS model, network configuration, and camera settings. For more information, visit https://www.qnap.com/go/qvr-nas-selector .
[QVR Elite] License Type	Standard MP4 file based
[QVR Elite] User-defined trigger events	Subscription-based
[QVR Elite] QVR Pro Client (Desktop)	Tak
[QVR Elite] QVR Pro Client (Mobile)	Windows, macOS, and QNAP HybridDesk Station
[QVR Elite] Recording camera streams	Android and iOS
[QVR Elite] Free built-in camera channels	H.264
[QVR Elite] Expandable camera channels	2
[QVR Pro Client] Live 4K H.265 (6M) channel	Developing
Number @ 8 x 1080P H.264 recording channels (Use HybridDesktop Platform) (Expected)	N/A
[QVR Pro Client] Live 1080P H.264 (5M) channel	N/A
Number @ 8 x 1080P H.264 recording channels (Use HybridDesktop Platform) (Expected)	N/A
[QVR Pro Client] Live 720P (3M) H.264 channel	N/A
Number @ 8 x 1080P H.264 recording channels (Use HybridDesktop Platform) (Expected)	N/A
QVR Center	Tak
[QVR Center] Log management	Note: At least 4 GB RAM is required.
[QVR Center] Central monitoring across multiple servers	Tak

Zawartość opakowania

TVS-h877AX
 Kabel Ethernet 10GBASE-T x 1
 Przewód zasilający x 1
 Śruby z łbem płaskim x 32 (do dysku twardego 3,5
 Śruby z łbem płaskim x 24 (do dysku twardego 2,5
 Klucze do tacki dysku x 2
 Skrócona instrukcja instalacji (QIG)